

JCB COMPACT TRACTORS | 331HST/335HST



GROUND CARE

# FAST FACTS

- 2 models JCB 331HST and JCB 335HST with 4 cylinder, diesel engines
- 3 range hydrostatic transmission with selectable 2/4 wheel drive and cruise control
- Independent mid and rear PTO drives optional cutting decks and multitude of application specific attachments
- Category I three point linkage
- Ergonomic layout for optimum comfort and ease of operation



## JCB COMPACT TRACTORS | 331HST/335HST



ENGINE POWER	23.1kW (31hp) – 26.1kW (35hp)
MAX. TRAVEL SPEED	25km/h (15.5mph)

### STATIC DIMENSIONS

Machine model	331 HST/335HST
	mm (in)
Overall length	3690 (145.3)
Maximum height over ROPS	2400 (94.5)
Ground clearance	350 (13.8)

Machine model	331 HST/335HST
	mm (in)
Overall width (with turf tyres)	1465 (57.7)
Wheelbase	1680 (66.1)

### ENGINE

Machine model	331 HST/335HST
Type	4 Cylinder Diesel MHI
Capacity	cc 1500 / 1758

### TURNING RADIUS

Turning radius (without braking) – 2.9m

### TRANSMISSION

Type	Hydrostatic
Gear selection forward & reverse	3x3
Diff lock	Foot operated
PTO	hp 24 / 26
Mid PTO	rpm 2100
Rear PTO	rpm 540
Lift capacity at lift point	kg (lb) 1000 (2205)

### OPERATING WEIGHTS

Machine model	331 HST/335HST
Operating weight	kg (lb) 1439 (3172) / 1465 (3230)

### TOWING CAPACITY

Maximum vertical load on draw bar	kg (lb)	500 (1102)
Maximum towing capacity unbraked	kg (lb)	1400 (3086)
Inertia braked capacity	kg (lb)	6000 (13227)

### TYRES

Front Standard Turf	27/10.50LLx15
Rear Standard Turf	41/14.00x20

### STANDARD / OPTIONAL EQUIPMENT

**Standard equipment:** Engine Tier II compliant, foldable ROPS and seat belt, mid and rear PTO, Category I three point linkage, selectable 2/4WD, diff lock, HST drive, weight frame, auto headland management and cruise control.

**Optional equipment:** 60" mid mount cutting deck, agricultural tyres, industrial tyres, front counter weights, 60" or 72" rear cutting deck, loader and backhoe.



JCB cares for the environment. This paper has been produced without the use of elemental chlorine chemicals in the bleaching process.

JCB Groundcare, Rocester, Staffordshire ST14 5JR. Tel: 01889 590312. Fax: 01889 593048. [www.jcb.co.uk](http://www.jcb.co.uk)

JCB reserves the right to change specifications without notice. Illustrations shown may include optional equipment and accessories. The JCB logo is a registered trademark of J C Bamford Excavators Ltd.



9999/5261 5/06 Issue 2

A Product of Hard Work