

# JCB RM1500R & RM1800R | REAR-MOUNT MOWER



A Product  
of Hard Work

# FAST FACTS

- Integral roller prevents scalping
- Triple cutting blades cut closer and more accurately
- Variable height adjustment gives maximum versatility
- Suitability to both fine and rough cutting operations increases flexibility
- Category I three-point linkage adapts to a large number of machines



## JCB REAR-MOUNT MOWER | RM1500R & RM1800R



### DIMENSIONS

Machine model		RM1500R	RM1800R
Working width	mm (in)	1500 (60)	1800 (70)
Cutting height	mm (in)	0 – 76 (0 – 3)	0 – 76 (0 – 3)
Approximate weight	kg (lb)	183 (403)	226 (498)
Tractor fitment		323 / 327	331 / 335

### CUTTING SYSTEM

Machine model		RM1500R & RM1800R
Discharge		Rear
Number of blades		3
Blade speed	m/s (ft/min)	82 (16141)
Height adjustment		On castor wheels

### DRIVE SYSTEM

Machine model		RM1500R & RM1800R
Main drive		Rear PTO 540rpm
Spindle drive		Belt
Power requirement – RM1500R	hp (kW)	15 (11)
Power requirement – RM1800R	hp (kW)	20 (15)

### STANDARD EQUIPMENT

All necessary equipment for fitment to tractor; remote greasing point, anti-scalp roller, heavy duty castors, variable height adjustment system.

### OPTIONAL EQUIPMENT

Mulching kit.



JCB Attachments Limited, Rugeley, Staffordshire WS15 2WA.  
Tel: 01889 572796. Fax: 01889 570043. Web: <http://www.jcb.com>

JCB cares for the environment.  
This paper has been produced  
without the use of elemental chlorine  
chemicals in the bleaching process.

JCB reserves the right to change specifications without notice. Illustrations shown may include optional equipment and accessories.  
The JCB logo is a registered trademark of J C Bamford Excavators Ltd.



9814/0196 9/06 Issue 1

A Product  
of Hard Work