

# Loaders.

## Load up then take a load off.

Take a load off your mind and your to-do list with the fast cycle times and impressive lift capacities of the John Deere Quick-Park loaders. Enjoy superior loading performance and unparalleled efficiency with a regen function to speed cycle times. Not only will you save time loading you'll also save time taking them off and putting them on – just three

minutes or less, no tools needed. Plus a standard attachment carrier means you won't even have to bother taking the loader off to switch jobs. Key high strength cast components ensure superior durability where you need it most, providing you with a loader that can rise to the most demanding applications.

### WHAT TO LOOK FOR IN A LOADER

		2000 TWENTY 200CX Loader	3000 TWENTY 300CX	4000 TWENTY 400CX
<b>Lift Capacities:</b> Pivot pin vs. 500 mm ahead: The lift capacity at pivot pin is a gross measure of loader lifting ability. The lift capacity 500 mm ahead of pivot point is often the better measure of working lift capacity	Lift capacity at pivot pin (max. height)	410 kg (902 lb)	678 kg (1492 lb)	1081 kg (2383 lb)
<b>Lift and reach:</b> Consider how high and far you need a loader to reach. Do you need to load a truck, for instance?	Maximum lift height at pivot pin	1993 mm (78.5 in)	2571 mm (101.2 in)	2865 mm (112.8 in)
	Reach at max. height	750 mm (29.5 in)	533 mm (20.1 in)	629 mm (24.8 in)
<b>Breakout Force:</b> The higher the breakout force, the easier it is to fill the bucket.	Breakout force at pivot pin	9960 N (2239 lb)	14420 N (3242 lb)	15280 N (3435 lb)
<b>Fast Cycle Times:</b> Loaders do repetitive tasks and saving a second or two each cycle can really add up. Besides fast raising, lowering and dump times, steep dump and rollback angles also contribute to faster cycle times.	Dump angle	38 deg.	45 deg.	45 deg.
	Rollback angle	25 deg.	31 deg.	43 deg.
	Loader raising time	3.19 seconds	3.57 seconds	3.68 seconds
	Loader lowering time	1.95 seconds	2.1 seconds	2.48 seconds
	Bucket dump time (regen)	3.19 (1.25) seconds	3.04 (1.24) seconds	2.76 (1.0) seconds
	Bucket rollback time	1.95 seconds	1.79 seconds	1.87 seconds

### UPGRADE YOUR LOADER




Convenient 4-in-1 bucket is perfect for loading or grabbing debris.



Pallet forks adjust in width to accommodate larger loads.



Single tine spear makes quick work of moving large bales.



Materials bucket is great for carrying a variety of heavy or light materials.



Proper ballasting enables quicker, more efficient loading.

## 200CX Loader for Small Chassis

- Quick Park Loader
- 9,960 N (2,239 lb./ft.) Breakout Force\*
- Off/on in 3 minutes or less



## 300CX Loader for Medium Chassis

- Quick Park Loader
- 14,420 N (3,242 lb./ft.) Breakout Force\*
- Off/on in 3 minutes or less
- Easy-to-each grease nipples



## 400CX Loader for Large Chassis

- Quick Park Loader
- Self levelling
- 15,280 N (3,435 lb./ft.) Breakout Force\*
- Off/on in 3 minutes or less
- Easy-to-reach grease nipples



\* Lift capacity (breakout force) listed is at pivot pin.