

Specifications

2320

2520

2720

3320

| | 2320 | 2520 | 2720 | 3320 |
|------------------------------------|--------------------------------------------------|--------------------------------------------------|----------------------------------------------|------------------------------------------------------------|
| Engine | Yanmar | Yanmar | Yanmar | Yanmar |
| Type | 3 cylinder diesel | 3 cylinder diesel | 3 cylinder diesel | 3 cylinder diesel |
| Gross Power | 17.9 kW (24 hp) | 19.6 kW (26.7 hp) @ 2600 rpm | 23.1 kW 31.4 hp @ 2500 rpm | 24.2 kW (32.4 hp) |
| Net Power ECE R24 | 16.9 kW (23 hp) | 19.1 kW (26.0 hp) @ 2600 rpm | 22.4 kW (30.5 hp) @ 2500 rpm | 23.1 kW (31 hp) |
| PTO Power eHydro | 13 kW (18 hp) | 15 kW (20 hp) | 17.5 kW (24 hp) | 19 kW (25 hp) |
| Displacement | 1.1 ltr | 1.3 ltr | 1.6 ltr | 1.6 ltr |
| Max Torque | 63 Nm @ 1900 rpm | 85 Nm @ 1200 rpm | 106 Nm @ 1000 rpm | 107 Nm @ 1200 rpm |
| Engine RPM | 3000 RPM | 2600 rpm | 2500 rpm | 2600 rpm |
| Air Cleaner | Dry type w/ safety element | Dry type w/ safety element | Dry type w/ safety element | Dry type w/ safety element and restriction indicator light |
| Fuel Tank Capacity | 23 ltr | 27 ltr | 27 ltr | Open Station – 51 ltr Cab – 45 ltr |
| Drivetrain | | | | |
| Transmission – Gear | N/A | N/A | N/A | N/A |
| Transmission – Hydro | Hydro two-pedal automatic | Hydro two-pedal automatic | Hydro two-pedal automatic | eHydro two-pedal automatic |
| Max. Speed | 20 km/h (12.4 mph) | 22 km/h (13.7 mph) | 22 km/h (13.7 mph) | 33 km/h (20.5 mph) |
| Clutch | | | | |
| – eHST | No | No | No | No |
| – PowrReverser | N/A | N/A | N/A | N/A |
| Brakes | Wet disc | Wet disc | Wet disc | Wet disc |
| Steering | Power steering | Power steering | Power steering | Power steering |
| Differential Lock | Standard | Standard | Standard | Standard |
| Four-Wheel Drive | Standard | Standard | Standard | Standard |
| Hydraulic System | | | | |
| Type | Open centre | Open centre | Open centre | Open centre |
| Pressure | 167 bar (16700 kPa) | 167 (16700 kPa) | 167 (16700 kPa) | 172 bar (17238 kPa) |
| Total Flow | 31.8 (l/min) | 39.6 (l/min) | 39.6 (l/min) | 52.5 (l/min) |
| Implement | | 20.8 (l/min) | 20.8 (l/min) | 32.5 (l/min) |
| Steering | | 18.8 (l/min) | 18.8 (l/min) | 20 (l/min) |
| Cat 1 3-Point Hitch | Standard | Standard | Standard | Standard |
| Lift Capacity | | | | |
| – at lift points | 650 kg | 650 kg | 650 kg | 1148 kg |
| – 24 in. (610 mm) behind lift ends | 522 kg | 522 kg | 522 kg | 999 kg |
| PTO | | | | |
| Type | Independent | Independent | Independent | Independent |
| Location | Standard rear mid standard and front optional | Standard rear mid standard and front optional | Standard rear mid standard and front opt. | Standard rear mid* standard and front optional |
| Speed | 540 rear 2100 mid and front | 540 rear 2100 mid and front | 540 rear 2100 mid and front | 540 rear 2100 mid and front |
| Clutch/Brake | Wet multi disc | Wet multi disc | Wet multi disc | Wet multi disc |
| Safety | | | | |
| ROPS/Cab | Complies with ASAE, OSH Standards | Complies with ASAE, OSH Standards | Complies with ASAE, OSH Standards | Complies with ASAE, OSH Standards |
| Driver Safety System | | | | |
| – PTO brake | Standard | Standard | Standard | Standard |
| – Operator present | Standard | Standard | Standard | Standard |
| Dimensions | | | | |
| Total Length with 3-Point Hitch | 2845 mm | 2835 mm | 2835 mm | 3230 mm |
| Total Width | 1295 mm | 1295 – 1360 mm | 1295 – 1360 mm | 1323 – 1728 mm |
| Wheel Base | 1600 mm | 1655 mm | 1655 mm | 1727 mm |
| Height | | | | |
| – ROPS | 2261 – 2304 mm | 2264 – 2279 mm | 2264 – 2279 mm | 2332 – 2370 mm |
| – Cab | 1891 – 1990 mm | 1998 – 2000 mm | 1998 – 2000 mm | 2117 – 2152 mm |
| Weight | | | | |
| – Empty Weight w/Cab | 805 kg / 1005 kg | 915 kg / 1015 kg | 915 kg / 1015 kg | 1400 kg / 1700 kg |
| – Total Permissible | 2000 kg | 2000 kg | 2000 kg | 3180 kg |
| – Front Axle | 880 kg | 880 kg | 880 kg | 1450 kg |
| – Rear Axle | 1600 kg | 1600 kg | 1600 kg | 2000 kg |
| Towing Capacity | 2000 kg | 2000 kg | 2000 kg | 4000 kg |
| Tyres | | | | |
| Turf | | | | |
| – Front | 23x8.5-12 | 24x8.5-14 | 24x8.5-14 | 27x8.50-15 4PR |
| – Rear | 31x13.5-15 | 36x14-15 | 36x14-15 | 41x14.00-20 4PR |
| Golf | | | | |
| – Front | – | – | – | 25/10.50LLx15 6PR |
| – Rear | – | – | – | 41LLx18-16.1 6PR |
| Industrial | | | | |
| – Front | 23x8.50 | 23x8.50-12 | 23x8.50-12 | 25x8.50-14 6PR |
| – Rear | 12-16.5 | 14-17.5 | 14-17.5 | 15.00-19.5 6PR |
| Industrial | | | | |
| – Front | – | – | – | 27x8.5-15 6PR |
| – Rear | – | – | – | 43x16.00-20 4PR |
| AG | | | | |
| – Front | – | – | – | 7.00-14 6PR |
| – Rear | – | – | – | 11.2-24 6PR |

* On PowrReverser optional

| | | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Yanmar 3 cylinder diesel turbocharged 27.7 kW (37.7 hp) 26.6 kW (35.7 hp) 23 kW (30 hp) 1.5 ltr 116 Nm @ 1400 rpm 2600 rpm Dry type w/ safety element and restriction indicator light Open Station – 51 ltr Cab – 45 ltr | Yanmar 3 cylinder diesel turbocharged/intercooler 32.6 kW (43.7 hp) 32.4 kW (43.4 hp) 26 kW (35 hp) 1.5 ltr 137 Nm @ 1560 rpm 2600 rpm Dry type w/ safety element and restriction indicator light Open Station – 51 ltr Cab – 52 ltr | John Deere Turbocharged 4 cylinder diesel (integrated fuel system) 35.5 kW (47.6 hp) 35 kW (46.9 hp) 30 kW (40 hp) 2.4 ltr 174 Nm @ 1440 rpm 2400 rpm Dry type w/ safety element and restriction indicator light Open Station – 55 ltr Cab – 52 ltr | John Deere Turbocharged 4 cylinder diesel (integrated fuel system) 39.2 kW (52.6 hp) 39 kW (52.3 hp) 34 kW (45 hp) 2.4 ltr 194 Nm @ 1440 rpm 2400 rpm Dry type w/ safety element and restriction indicator light Open Station – 55 ltr Cab – 52 ltr | John Deere Turbocharged 4 cylinder diesel (integrated fuel system) 46 kW (62 hp) 42 kW (56.5 hp) 37 kW (50 hp) 2.4 ltr 210 Nm @ 1440 rpm 2400 rpm Dry type w/ safety element and restriction indicator light Open Station – 55 ltr |
| 12x12 PowrReverser eHydro two-pedal automatic 33 km/h (20.5 mph) | N/A eHydro two-pedal automatic 33 km/h (20.5 mph) | 12x12 PowrReverser eHydro two-pedal automatic 30 km/h (18.6 mph) | 12x12 PowrReverser eHydro two-pedal automatic 30 km/h (18.6 mph) | N/A eHydro two-pedal automatic 30 km/h (18.6 mph) |
| No Wet multi disc Wet disc Power steering Standard Standard | No N/A Wet disc Power steering Standard Standard | No Wet multi disc Wet disc Power steering Standard Standard | No Wet multi disc Wet disc Power steering Standard Standard | No N/A Wet disc Power steering Standard Standard |
| Open centre 172 bar (17238 kPa) 52.5 (l/min) 32.5 (l/min) 20 (l/min) Standard | Open centre 172 bar (17238 kPa) 52.5 (l/min) 32.5 (l/min) 20 (l/min) Standard | Open centre 172 bar (17238 kPa) 64.6 (l/min) 45.3 (l/min) 19.3 (l/min) Standard | Open centre 172 bar (17238 kPa) 64.6 (l/min) 45.3 (l/min) 19.3 (l/min) Standard | Open centre 172 bar (17238 kPa) 64.6 (l/min) 46.3 (l/min) 19.3 (l/min) Standard |
| 1148 kg 999 kg | 1148 kg 999 kg | 1423 kg 1134 kg | 1423 kg 1134 kg | 1419 kg 1134 kg |
| Independent Standard rear mid* standard and front optional 540 rear 2100 mid and front Wet multi disc | Independent Standard rear mid* standard and front optional 540 rear 2100 mid and front Wet multi disc | Independent Standard rear mid optional 540 and 540E rear 2100 mid Wet multi disc | Independent Standard rear mid optional 540 and 540E rear 2100 mid Wet multi disc | Independent Standard rear mid optional 540 and 540E rear 2100 mid Wet multi disc |
| Complies with ASAE, OSH Standards | Complies with ASAE, OSH Standards | Complies with ASAE, OSH Standards | Complies with ASAE, OSH Standards | Complies with ASAE, OSH Standards |
| Standard Standard | Standard Standard | Standard Standard | Standard Standard | Standard Standard |
| 3230 mm 1323 – 1728 mm 1727 mm | 3230 mm 1323 – 1728 mm 1727 mm | 3454 mm 1667 – 2334 mm 1816 mm | 3454 mm 1667 – 2334 mm 1816 mm | 3454 mm 1667 – 2334 mm 1816 mm |
| 2332 – 2370 mm 2117 – 2152 mm | 2332 – 2370 mm 2117 – 2152 mm | 2372 – 2468 mm 2168 – 2266 mm | 2372 – 2468 mm 2168 – 2266 mm | 2372 – 2468 mm 2168 – 2266 mm |
| 1400 kg / 1700 kg 3180 kg 1450 kg 2000 kg 4000 kg | 1400 kg / 1700 kg 3180 kg 1450 kg 2000 kg 4000 kg | 1680 kg / 1980 kg 4000 kg 1600 kg 2400 kg 5000 kg | 1680 kg / 1980 kg 4000 kg 1600 kg 2400 kg 5000 kg | 1680 kg / 1980 kg 4000 kg 1600 kg 2400 kg 5000 kg |
| 27x8.50-15 4PR 41x14.00-20 4PR | 27x8.50-15 4PR 41x14.00-20 4PR | 27x10.50-15 4PR 44x18.00-20 4PR | 27x10.50-15 4PR 44x18.00-20 4PR | 27x10.50-15 4PR 44x18.00-20 4PR |
| 25/10.50LLx15 6PR 41LLx18-16.1 6PR | 25/10.50LLx15 6PR 41LLx18-16.1 6PR | 27x12LL-15 6PR 22.5LL-16.1 6PR | 27x12LL-15 6PR 22.5LL-16.1 6PR | 27x12LL-15 6PR 22.5LL-16.1 6PR |
| 25x8.50-14 6PR 15.00-19.5 6PR | 25x8.50-14 6PR 15.00-19.5 6PR | 10.00-16.5 6PR 17.5L-24 8PR | 10.00-16.5 6PR 17.5L-24 8PR | 10.00-16.5 6PR 17.5L-24 8PR |
| 27x8.5-15 6PR 43x16.00-20 4PR | 27x8.5-15 6PR 43x16.00-20 4PR | – – | – – | – – |
| 7.00-14 6PR 11.2-24 6PR | 7.00-14 6PR 11.2-24 6PR | 8.00-16 6PR 13.6-28 4PR | 8.00-16 6PR 13.6-28 4PR | 8.00-16 6PR 13.6-28 4PR |