

The comfort reference.

Even though the 1505* and 1515* are large scale mowers, focus is on the little details that are the hallmarks of true excellence in comfort and reliability. That's why over the years of development, these two high performance models have been continuously improved.*

*Not available in the UK.

Premium Comfort Cab

Optional factory fitted spacious cabs are the ultimate in comfort. Cab is vibration isolated and features very low noise level. With Cab, the mower is equipped with air suspended seat for outstanding ride comfort. Optional, factory fitted air conditioning is available.



All-in-one command

The ergonomically designed, adjustable CommandArm armrest with integrated controls is standard on the 1505 and 1515. It moves with the seat and allows easy control over your machine.



Road drive comfort

Comfort seats and front deck suspension (gas pressure accumulator) automatically activated during road use provide first class comfort.



Low noise level

Hydraulically driven blades make machine operation noticeably quiet. Also low rated engine speed and the advanced exhaust system result in reduced mowing noise which is beneficial to the environment and the operator.



Efficient cutting performance

Hydraulic deck drive technology provides constant blade speed even in tough conditions. Hydraulic quick couplers ensure easy mounting of the deck or any hydraulically driven attachments.

Comfort Mower	1505*	1515*
Engine type	Yanmar	Yanmar
Rated Engine hp (ISO)	35 kW (48 hp)	35 kW (48 hp)
97/68/EC @ rated engine rpm		
Rated Engine hp, ECE-R24 @ engine rpm	31 kW (42 hp)	31 kW (42 hp)
Rated engine speed (rpm)	2600	2600
Max. torque (Nm) @ rpm	120@1700	120@1700
Cylinders	4	4
Displacement (cc)	2190	2190
Injection type	Direct	Direct
Air Cleaner	Dual-Stamp with restriction indicator	Dual-Stamp with restriction indicator
Average fuel consumption (mowing condition) (l/h)	5.7	5.7
Fuel Tank Capacity (ltr)	50	50
Transmission	Hydrostatic, wheel motors	Hydrostatic, wheel motors
Travel Speeds (Infinite)		
Forward Max km/h (mph)	25 (15)	25 (15)
Forward Low range km/h (mph)	16 (10)	16 (10)
Speed and Direction Control	Single pedal servo system	Single pedal servo system
Brakes	Wet on wheel motors	Wet on wheel motors
Transmission Oil Cooler	Integrated oil and coolant cooler	Integrated oil and coolant cooler
4WD	Wheel motors	Wheel motors
Differential lock	Standard	Standard
Weight transfer	Standard	Standard
Dimensions		
Vehicle Height w/o Cab m (in)	1.43 (56.3)	1.43 (56.3)
Vehicle Height w/ Cab m (in)	2.09 (82.3)	2.09 (82.3)
Overall Length w/o Mower (m)	2.28	2.28
Ground Clearance (m)	0.23	0.23
Wheelbase (m)	1.31	1.31
Weight		
Weight including deck w/o Cab (kg)	1,320	1,575
Weight including deck and Cab (kg)	1,495	1,750
Tyres		
Front	26x12-12 6 PR	26x12-12 6 PR
Rear	20x10-10 4 PR	20x10-10 4 PR
Seat		
	Grammer Maximo M for OOS or XXL for Cab	Grammer Maximo M for OOS or XXL for Cab
* Not available in the UK		



1515 front and wing deck advantage
Reach difficult spots, like roadsides and areas close to water! Prevent possible damage from trees or kerbs and other potential obstructions while the deck moves rearwards and inwards!



Serviceability
Optimum service access keeps maintenance time to a minimum. Diagnostics are simplified with LED lights and a "heartbeat". Also, from a rugged frame, to Kevlar mower deck belts, to a fifth-generation hydraulic system, it's clear these mowers are ready for a lifetime of service.

Mower Decks	fits 1505	fits 1505	fits 1505	fits 1515
Type and cutting width m (in)	Side Discharge 1.80 (71)	Rear Discharge 1.83 (72)	Rear Discharge 2.23 (88)	Total 2.85 (112), Front 1.80 (71), Side Wing 1.20 (47) RD
Construction	Fabricated	Fabricated Fast Back	Fabricated	Fabricated
Thickness (mm)	4	4	4	4
Height of Cut mm (in)	13 – 105 (0.5 – 4.1)	25 – 152 (1 – 6)	13 – 105 (0.5 – 4.1)	Front deck: 13 – 105 (0.5 – 4.1) Side deck: 13 – 105 (0.5 – 4.1)
Transport Width m (in)	2.16 (85) with chute	1.88 (74)	2.05 (80.7)	2.04 (80.3)
Mulch Kit	N/A	Available	N/A	Available