

Heavy duty, that's what counts.



Comfort
The Deluxe seat ensures all-day operator comfort.



Convenience
With Sit-on-Seat Diagnostics, everything from reel controls to machine diagnostics and bilingual codes are in the operator's sight.



John Deere 2653B is uniquely designed to excel in all areas: excellent quality of cut, superior operator comfort and ease of use combined with unmatched access to all service items plus high durability and reliability.

3 Gang Reel Mower	2653B
Engine type	
Rated Engine hp (ISO) 97/68/EC @ rated engine rpm	Yanmar 14.6 kW (19.5 hp)
Rated Engine hp, ECE-R24 @ engine rpm	14.2 kW (19 hp)
Rated engine speed (rpm)	3000
Cylinders	3
Displacement (cc)	854
Injection type	Indirect
Air cleaner	Dual-Stamp with restriction indicator
Fuel Tank (ltr)	28
Transmission	
Hydrostatic	
Travel speeds	
Forward Max km/h (mph)	14 (8.5)
Low range km/h (mph)	8 (5)
Speed and direction control	2-pedal hydrostatic control
Brakes	Hydrostatic
Drive	3 Wheel motors
Dimensions	
Transport Width m (in)	1.60 (63) / 1.90 (75)
Vehicle Height w/ ROPS (m)	2.08
Overall length w. Cutting Units (m)	2.35
Weight w. Cutting Units (kg)	860
Tyres	
Front	20x10-10
Rear	20x10-8
Cutting units	
Type (cm)	66
Diameter cm (in)	17.8 (7)
Number of blades	5/8
Head type	Fixed or floating
Total Cutting Width (cm)	183
Type (cm)	76
Diameter cm (in)	17.8 (7)
Number of blades	5/8
Head type	Fixed or floating
Total Cutting Width (cm)	213



All terrain
The 2653B features a powerful hydraulic drive system, providing equal traction to all wheels and eliminating the need for weight transfer.



Durable cutting Unit
Both the 66 cm (26 in) and 76 cm (30 in) cutting units roll on and off mounting arms quickly and easily for routine service.

For more information, please see our Golf brochure.