

Consider yourself out-maneuvred. Z-Trak.



There's only one simple solution to cutting down your mowing time and coming in under budget.

How? Great manoeuvrability combined with a powerful engine, high capacity deck and reliability.

With numbers like a minimum of 20% less operating time than a front mower, it's easy to see how fast the savings can add up.



Power to perform

The 997 diesel Z-Trak is equipped with a direct injection Yanmar diesel engine, which provides more displacement and peak torque than most competitors – this enables operators to maximise acres mowed per hour.



Heavy duty design

Shaft-driven mower deck, hydraulic PTO clutch, single-body dual-unitised pump and strong chassis are the key elements for proving long life and durability.



Deck choice

Three choices for decks: a side discharge or rear discharge 1.52 m (60 in) deck and for more productivity, a 1.83 m (72 in) side discharge deck – all manufactured from 7 gauge (4.5 mm) steel.

Zero Turn Mower	997
Engine type	
Rated Engine hp (ISO) 97/68/EC @ rated engine rpm	Yanmar Diesel 23 kW (31 hp)
Rated Engine hp, ECE-R24 @ engine rpm	22 kW (29 hp)
Rated engine speed (rpm)	3000
Max. torque (Nm) @ rpm	86@1800
Displacement (cc)	1330
Cylinders	3
Air Cleaner	Dual-Stamp with restriction indicator
Injection type	Direct
Fuel Tank Capacity (ltr)	45.5
Average fuel consumption (mowing condition) (ltr/h)	3.3
Transmission	
Travel speed, FORWARD km/h (mph)	0 – 18.5 (0 – 11.5)
Travel speed, REVERSE km/h (mph)	0 – 8 (0 – 5)
Hydraulic Oil Cooler	Radiator type
Drive Tyres	26x12 - 12 4 PR
Caster Wheel Size	15x6 - 6
Braking	Twin levers
Park Brake	Dry disc, hand lever actuated
PTO clutch	Wet multi-disc, modulated
PTO drive	Shaft
PTO engagement	Electro-hydraulic
Seat	
	Deluxe with armrests, suspension option
Dimensions	
Overall Length m (in)	2.43 (96)
Height folded ROPS/with ROPS m (in)	1.51 (59.5) / 1.93 (74.8) w/ OSHA ROPS
Weight (kg)	805
Mower Decks	
Lift system	Electro-Hydraulic, foot actuated
Height of Cut Adjustment	Dial gauge, assisted by hydraulic deck lift

Mower Decks			
Type and cutting Width in m (in)	Rear discharge 1.53 (60)	Side discharge 1.53 (60)	Side discharge 1.83 (72)
Construction	Fabricated	7-Iron One-piece stamped steel	7-Iron One-piece stamped steel
Thickness mm (gauge)	4.5 (7)	4.5 (7)	4.5 (7)
Height of Cut mm (in)	38-127 (1.5 - 5)	38-127 (1.5 - 5)	38-127 (1.5 - 5)
Transport Width m (in)	1.57 (62)	1.87 (74) w/chute	2.18 (86) w/chute
Mulch Kit	N/A	optional	optional



Easy deck lift

For deck lift, just press the electrical foot pedal switch to lift.



Simple Height of Cut adjustment

Best in class deck adjustment thanks to the Height of Cut selector that is well located on the right hand control panel.



Outstanding operator Comfort

One piece, high-back, deep cushioned seat with standard armrest and excellent visibility to the operator controls, which are located on the right hand side including the electrical PTO switch.